



章丘市金属颜料有限公司

ZHANGQIU METALLIC PIGMENT CO., LTD

Sangyuan Industrial Park, Zhangqiu City,

Shandong Province 250203, China.

Tel; 86-531-83261860 Fax; 86-531-83362598

PRODUCT DATA SHEET

ZL-201W-B06

HYDRO-ALUMINUM POWDERS FOR CONCRETE

TECHNICAL DATA

Metal content (+/-2%)..... 98.4

Active Aluminum Content (>%).....94

Gas time(Mins).....18-22

Gas volume(>ml).....75

Stearic acid(<%)..... 1.6

APPLICATIONS GUIDELINES

ZL-201W-B06 is applied to the production of aerated concrete.

RECOMMENDE PROCEDURE

The aluminum powder is added in the process of producing concrete, together with coal ash, cement, lime, sand, cleaning agent and water, etc.

SHELF TIME: SIX MONTH

All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.