

章丘市金属颜料有限公司 ZHANGQIU METALLIC PIGMENT CO., LTD

Sangyuan Industrial Park, Zhangqiu City, Shandong Province 250203, China. Tel: 86-531-83261860 Fax: 86-531-83362598 Http://zq1987.com Email:info1@zqmetallic.com

PRODUCT DATA SHEET

VMP-1115PM

Vacuum Metallized Pigments

TECHNICAL DATA

Non-Volatile Content10% by weight

Average Particle Size.....11±1 microns

Solvent.....Glycol PM

APPLICATIONS GUIDELINES

VMP-1115PM are suitable for spray paint, printing ink, etc.

RECOMMENDED USAGE

Printing Ink *Offset :10% *Gravure:20-40% *Screen:20%-70% Coatings *plain color: 4-6% *mix color: 3%

The products should be mixed thoroughly before incorporation to assure a homogenous mix of the pigment flakes throughout the dispersion. As with all aluminium pigments, excessive shear should not be used.

All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.