

章丘市金属颜料有限公司 ZHANGQIU METALLIC PIGMENT CO., LTD

Sangyuan Industrial Park, Zhangqiu City, Shandong Province 250203, China. Tel: 86-531-83261860 Fax: 86-531-83362598

ZQ-13625

ALUMINUM PASTE

PRODUCT DATA SHEET

TECHNICAL DATA

NON-LEAFING

Screen Analysis99% minimum through 200 mesh

(wet method)

Non-Volatile Content72.0% (± 2.0%) by weight

Average Particle Size......36 ±1 microns

Solvent.....High Aromatic

APPLICATIONS GUIDELINES

ZQ-13625 applied to the metal and plastic coatings, and widely use in coil, engineering machinery, thermosetting plastic acrylic coatings system.

RECOMMENDED DISPERSION PROCEDURE

Under slow agitation, adding in some amount of solvent to the aluminum paste to develop a smooth pigment slurry. Then add further solvent of choice and vehicle system where needed.

All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.