



# 章丘市金属颜料有限公司

ZHANGQIU METALLIC PIGMENT CO., LTD

Sangyuan Industrial Park, Zhangqiu City, Shandong Province 250203, China.

Tel:86-531-83261860 Fax: 86-531-83362598

## PRODUCT DATA SHEET

# ZQ-1281

## ALUMINUM PASTE

### TECHNICAL DATA

#### • NON-LEAFING

**Grade** .....325 Mesh Grade

**Screen Analysis** .....99.00% minimum through 325 mesh  
(wet method)

**Non-Volatile Content** .....72.0% ( $\pm 2.0\%$ ) by weight

**Average Particle Size**.....28  $\pm 1$  microns

**Solvent**.....HA

### APPLICATIONS GUIDELINES

ZQ-1281 imparts a smooth bright sparkling effect and is widely used in the 3C markets, automotive OEM and auto refinish, coil, and general industrial coatings.

### RECOMMENDED DISPERSION PROCEDURE

Under slow agitation, adding sufficient amount of solvent to the aluminum paste to develop a smooth pigment slurry. Then add further solvent of choice and vehicle system where needed.

All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.